WAREHOUSE OCCUPANCIES

OWNER / OCCUPANT INSPECTION INFORMATION

The B.C. Fire Code requires building owners and occupants to comply with the requirements on this checklist.

These requirements are in addition to those listed in the Fire Safety & You brochure.

WAREHOUSE USES INCLUDE:

- Warehousing and storage
- Shipping and receiving



FIRE DEPARTMENT

675 13th Ave Campbell River, BC V9W 6C1

250-286-6266 www.campbellriver.ca/fire



CHECKLIST: COMMON FIRE SERVICE REQUIREMENTS

Address: must be visible from road and lane, free from foliage, and in a contrasting colour.

Elec	ctrical equipment: must be free of dust, with clearance from combustibles.	
ope	ergency lighting: may be provided by battery packs with remote and attached heads. Must be erational, with no visible damage, with heads aimed in proper direction, and serviced and tagged really by a certified technician.	
	doors: must not be locked or blocked from either the inside or out. Must be unlocked from inside when the building is occupied.	
Exit	signs: must be visible and remain illuminated at all times when the building is occupied.	
Ехр	osures such as pallets or flammable items: should be noted as to location and type.	
with	e alarm systems: must have a working A/C power-on bulb and be in good working condition h no audible or visual damage. Must have a current service tag (within the last 12 months) and to-date logbook.	
	e doors: must not be blocked or wedged open, including stairwell doors. No door wedges to used.	
	hose cabinets: there must be clear access to cabinets, hose must be in good repair and nplete with nozzles.	
	hydrants : must be accessible, free of damage and serviced within the specified date. Private lrants require annual service, with records kept on site.	
Fire	lanes: must have an adequate clear width of six unobstructed metres from building.	
Fire	separations: must have no holes or openings that compromise their purpose.	
Forklifts: propane and gasoline-fired forklifts require a minimum rating 2A-10BC.		
	bage disposal: commercial containers must be located three metres from combustible ldings, and if inside, should have tight-fitting lids and be in fire-separated rooms.	
'No	Smoking' signs: must be posted in hazardous areas.	
Por	Portable fire extinguishers: must:	
	be located adjacent to corridors or aisles that provide access to exits.	
	be mounted in a visible location, accessible, and serviced and tagged at least once every 12 months by a certified technician.	
	Be full and functioning (no leaks, damage, corrosion, malfunctioning parts or clogged nozzles).	

Portable heaters: must be an approved type and kept away from combustibles.

have a current service tag (within the last 12 months) and up-to-date logbook.

Sprinkler and standpipe connections: must be capped, free of debris and accessible.

Sprinkler valves: must be in the open position, either locked and chained, or sealed and monitored electronically. No storage is permitted within 18 inches of the bottom of the sprinkler

Storage arrangement: maximum height of storage of commodities must comply with their

cylinders (full or empty) must be stored outside in a secure location.

Waste paper containers: in public areas must not be combustible.

Propane cylinders: cylinders inside must be connected to appliance/equipment and in use. All

Sprinkler system: must be inspected/tested by a qualified personnel at least once per year. Must

Have a minimum rating 2A-10BC

heads.

sprinkler system design.